



Lámparas de repuesto para luces empotradas en pavimento, elevadas, de aproximación, cono de viento y obstrucción

Esta es una lista de las lámparas de productos actuales de ADB como se muestran en nuestro catálogo y en nuestro sitio Web (www.adb-airfieldsolutions.com). Para lámparas adicionales, favor comunicarse con su representante de servicio. Cada lámpara se muestra en forma de cuadrícula de 1 pulgada para poder hacer mediciones.



Voltaje de la lámpara:	500W 230VAC
Descripción de la lámpara:	500W/230 AC incandescente PL10027
Designación FAA/ Aplicación:	L-864 para Ser Usadas En Faros Con Luz Doble 8.000H Montaje Rosca E40
Número de repuesto ADB:	PI10027

POINT LIGHTING CORPORATION

POINT FLASHING BEACON PFB FAA L-864

Tested & Certified by Intertek Testing Service (ETL) per FAA AC 150/5345-43

The PFB red flashing 300mm beacon is specified for use on stacks, towers and other aviation obstructions. The PFB has red Fresnel lenses and it is hinged at the midpoint for relamping. All exterior metal beacon parts are powdercoat painted aviation yellow as standard or anodized for corrosion resistance that meets the US Military Standard Salt Fog Test conducted per MIL-STD-810E, Method 509.3, Procedure I. The PFB beacon requires an external flasher POF-40040 or POC-60000 series controller to operate as specified.

Point Type	Lamps & Voltage	Options
PFB-30000	700: 700 watts, 120 volts 620: 620 watts, 120 volts 702: 700 watts, 230 volts 500: 500 watts, 230 volts	L: Lowering System Type FS: Flare Stack; High Temp EX: Explosion-Proof



FAA certified with FAA lamp number 48B

Input Power: 120v or 220-240v, 50/60 Hz
 Power: 1240 watts at 120v 10.3A (620w)
 1400 watts at 120v 11.7A (700w)
 Cable: 3-Conductor Type SOW (3-ft)
 Temp Rating: ± 55° C
 Mounting: 4 Holes on 13.25-inch circle

Replacement Parts

PL10090	Red Lens Set (4)
PL10093	Socket, 620 & 700w
PL10151	Socket, 500w
PL10026	Lamp 620w, 120v
PL10027	Lamp 500w, 230v
PL10097-700	Lamp 700w, 120v
PL10097-702	Lamp 700w, 230v

Instruction Sheet: IS30000
 Dimensions: Inches (mm)
 Height: 31.7 (805)
 Diameter: 15.0 (381)
 Weight: 80 lbs 36 kg
 Volume: 8.0 ft³ 0.23 m³

PFB-30000-620

